







**Triangle-Choker Type 1**  
**TCA - Aluminum**  
**TCS - Steel**








Stock No.	Width (Inches)	Ply	Vertical 	Choker 	Basket			
						75° 	60° 	45° 
*1-602	2	1	2400	1920	4800	4640	4160	3390
1-902	2	1	3200	2560	6400	6187	5547	4520
2-602	2	2	4800	3840	9600	9280	8320	6780
2-902	2	2	6400	5120	12800	12373	11093	9040
1-603	3	1	3600	2880	7200	6960	6240	5085
1-903	3	1	4800	3840	9600	9280	8320	6780
2-603	3	2	6660	5328	13320	12876	11544	9407
2-903	3	2	8880	7104	17760	17168	15392	12543
1-604	4	1	4800	3840	9600	9280	8320	6780
1-904	4	1	6400	5120	12800	12373	11093	9040
2-604	4	2	8640	6912	17280	16704	14976	12204
2-904	4	2	11520	9216	23040	22272	19968	16272
1-605	5	1	6000	4800	12000	11600	10400	8475
1-905	5	1	8000	6400	16000	15467	13867	11300
2-605	5	2	10500	8400	21000	20300	18200	14831
2-905	5	2	14000	11200	28000	27067	24267	19775
1-606	6	1	7200	5760	14400	13920	12480	10170
1-906	6	1	9600	7680	19200	18560	16640	13560
2-606	6	2	12240	9792	24480	23664	21216	17289
2-906	6	2	16320	13056	32640	31552	28288	23052
1-908	8	1	12800	10240	25600	24747	22187	18080
2-908	8	2	20480	16384	40960	39595	35499	28928
1-910	10	1	16000	12800	32000	30933	27733	22600
2-910	10	2	24000	19200	48000	46400	41600	33900
1-912	12	1	19200	15360	38400	37120	33280	27120
2-912	12	2	26880	21504	53760	51968	46592	37968

\* Use Prefix TCA or TCS to indicate metal in fittings



Rated Capacity in Pounds

**Triangle-Triangle Type 2 TTA - Aluminum TTS - Steel**

Stock No.	Width (Inches)	Ply	Vertical 	Basket			
					75° 	60° 	45° 
*1-602	2	1	2400	4800	4640	4160	3390
1-902	2	1	3200	6400	6187	5547	4520
2-602	2	2	4800	9600	9280	8320	6780
2-902	2	2	6400	12800	12373	11093	9040
1-603	3	1	3600	7200	6960	6240	5085
1-903	3	1	4800	9600	9280	8320	6780
2-603	3	2	6660	13320	12876	11544	9407
2-903	3	2	8880	17760	17168	15392	12543
1-604	4	1	4800	9600	9280	8320	6780
1-904	4	1	6400	12800	12373	11093	9040
2-604	4	2	8640	17280	16704	14976	12204
2-904	4	2	11520	23040	22272	19968	16272
1-605	5	1	6000	12000	11600	10400	8475
1-905	5	1	8000	16000	15467	13867	11300
2-605	5	2	10500	21000	20300	18200	14831
2-905	5	2	14000	28000	27067	24267	19775
1-606	6	1	7200	14400	13920	12480	10170
1-906	6	1	9600	19200	18560	16640	13560
2-606	6	2	12240	24480	23664	21216	17289
2-906	6	2	16320	32640	31552	28288	23052
1-908	8	1	12800	25600	24747	22187	18080
2-908	8	2	20480	40960	39595	35499	28928
1-910	10	1	16000	32000	30933	27733	22600
2-910	10	2	24000	48000	46400	41600	33900
1-912	12	1	19200	38400	37120	33280	27120
2-912	12	2	26880	53760	51968	46592	37968

\* Use Prefix TTA or TTS to indicate metal in fittings



Rated Capacity in Pounds

**WARNING:**  
**Aluminum fittings should not be used where fumes, vapors, sprays, mists or liquids of caustics are present.**